Research Microscope with Digital Imaging System

Specifications:

1) **Microscope Body:** Upright should be infinity corrected optical system. Upgradable to fluorescence attachment.

Nosepiece: Capable of having Seven objectives at a time.

Condenser: Suitable Condenser for Bright field & phase contrast

- 2) Illumination System: LED illumination with lifetime of 50,000hrs or more.
- 3) Evepiece lenses:

Option: 10x paired wide field eyepiece with **F.O.V. 20mm** or more with diopter adjustment on both sides

- 4) Eyepiece Tube: Three Way Trinocular tube for simultaneous view on microscope and Camera.
- 5) Stage: Rectangular stage with right hand control and adequate space for keeping two slides together for comparison.
- 6) Objectives:
 - a. Plan Achromat 4X (NA 0.10 or higher),
 - b. Plan Achromat 10X (NA 0.25 or higher),
 - c. Plan Achromat 20X (NA 0.40 or higher),
 - d. Plan Achromat 40X (NA 0.65 or higher),
 - e. Plan Achromat 100X Oil (NA 1.25 or higher)

7) Camera:

Digital Scientific color CMOS /CCD 5MP camera with pixel size of **2.2μm** X **2.2μm** or 3μm X 3μm suitable for Bright Field, Phase Contrast and Florescence application. Microscope, Objective, camera and software should be from same manufacturer.

8) Software: (Optional)

Licensed imaging software for Image Acquisition, Video recording, measurements like length, width, area etc. and manual cell.

9) Computer

Branded PC with i5 or move advanced processor, minimum 4 GB RAM, 1TB HDD or higher, Original Windows OS 8 or 10, DVD RW, at least 21 "TFT monitor, keyboard, mouse, online UPS.

- 10) Certifications: ISO, TUV, UL, USFDA, EUROPEAN CE (ANY TWO)
- 11) Demonstration: There should be provision for demonstration if required.
- 12). System should be provided with at least two year warranty and AMC.
- 13) On sight training by company expert annually for a period of two years.

HOD

Department of Pharmaceutical Sciences & Technology, MRSPTU, Bathinda